


LOUNGE CONCEPT II SUPREME

imensions	2.20 x 1.40 x 0.70 m
nell Coril® -	Any color shell
anels	Alupanels
/eight without water	250 Kg
/eight with water	800 Kg
olume	2.16 m3
QUIPMENT SPECIFICATIONS	
eats	2 lounged
lter	1 (1.1 m2)
over	1
/ater Capacity	550
rain Valve	1
ECHNICAL SPECIFICATIONS	
ets	41 *
rculation Pump	1 – 180 W
irculation / Massage Pump	-
assage Pump	1 - 1500 W
ower	1 – 1030 W
isinfection system	UV & Ozone
ontrol box with heater	1 – 3000 W
umination Multipoint	RGB Leds
LECTRICAL SPECIFICATIONS	
oltage	220-240 V ~ or 380-415 V ~
ax Absorbed Power	3370 W
equency	50 Hz
mperage	16A

* Number of jets may depend to the choice of the V-Jets option (standard configuration is C6+E6)

Note: the standard measures may vary ±2cm



IMPORTANT: Important: The equipment must be connected to an exclusive and permanent power line capable to support installed power. Lighting and electrical receptacles must be located at least 1.5 meters from the equipment.

The circuit ground wire must be provided to take advantage of the designed-in safety features of the equipment.

The electric installation must be in accordance with actual legislation.