


LOUNGE CONCEPT III SUPREME

TECHNICAL INFORMATION	
Dimensions	2.20 x 1.90 x 0.80 m
Shell Coril® -	Any color shell
Panels	AluPanels
Weight without water	400 Kg
Weight with water	1500 Kg
Volume	3.35 m3
EQUIPMENT SPECIFICATIONS	
Seats	3-5 (with 2 lounged)
Filter	2 (1.1 m2)
Cover	1
Water Capacity	1100
Drain Valve	1
TECHNICAL SPECIFICATIONS	
Jets	47 *
Circulation Pump	1 – 180 W
Circulation / Massage Pump	-
Massage Pump	2 –1500 W
Blower	1 – 1030 W
Disinfection system	UV & Ozone
Control box with heater	1 – 3000 W
Illumination Multipoint	RGB Leds
ELECTRICAL SPECIFICATIONS	
Voltage	220-240 V ~ or 380-415 V ~
Max Absorbed Power	3370 W
Frequency	50 Hz
Amperage	20A or 3x16A

^{*} Number of jets may depend to the choice of the V-Jets option (standard configuration is C6+E6+G6)

Note : the standard measures may vary $\pm 2 \text{cm}$



IMPORTANT: Important: The equipment must be connected to an exclusive and permanent power line capable to support installed power. Lighting and electrical receptacles must be located at least 1.5 meters from the equipment.

The circuit ground wire must be provided to take advantage of the designed-in safety features of the equipment.

The electric installation must be in accordance with actual legislation.