


ZETA 2.0

| Jata 32 Shell White Panels EcoWood Weight without water 300 Kg Weight without water 300 Kg Volume 24 m3 ECUIPMENT SPECIFICATIONS 2 (1 lounged) Filter 1 (5.5 m2) Circulation / Massage Pump 1 - 370/1500 W Massage Pump - Blower - Disinfection system Coone Control box with heater 1 - 3000 W Chromotherapy Leds Multipoint Cover 1 - 3000 W Water Capacity So50 I Drain Valve So50 I Vater Capacity So50 I Oral So | TECHNICAL INFORMATION | |
|---|------------------------------|----------------------------|
| Number Number Shell White Panels EcoWood Weight without water 300 Kg Weight with water 1150 Kg Volume 2.4 m3 EQUIPMENT SPECIFICATIONS 2 (1 lounged) Filter 1.5.5 m2) Circulation / Massage Pump 1.4 370/1500 W Massage Pump - Blower - Disinfection system Ozone Control box with heater 1.3000 W Chormotherapy Leds Multipoint Cover 350 I Water Capacity 850 I Drain Valve 20240 V~org 380-415 V~ Voltage 3200 W Kater SpecificATIONS 20240 V~org 380-415 V~ | Dimensions | 2.16 x 1.40 x 0.80 m |
| PanelsEcoWoodWeight without water300 KgWeight with water150 KgVolume24 m3EQUIPMENT SPECIFICATIONS2 (1 lounged)Seats2 (1 lounged)Filter1 (5.5 m2)Circulation / Massage Pump1 - 370/1500 WBlower0Disinfection system020neControl box with heater020neChromotherapy Leds1 - 3000 WCover1Water CapacitySo 1Water Capacity850 1Drain Valve1Voltage20-240 V ~ or 380-415 V ~Yoltage3370 WFrequency50 Hz | Jets | 32 |
| Weight without water300 KgWeight without water1150 KgVolume2.4 m3EQUIPMENT SPECIFICATIONSEQUIPMENT SPECIFICATIONSSeats2 (1 lounged)Filter1 (5.5 m2)Circulation / Massage Pump1 – 370/1500 WMassage Pump-Blower-Disinfection systemOzoneControl box with heater1 – 3000 WChromotherapy LedsMultipointCover1Water Capacity\$50 IDrain Valve1Voltage220-240 V ~ or 380-415 V ~Max Absorbed Power\$0 Hz | Shell | White |
| Weight with water1150 KgWolume2.4 m3EQUIPMENT SPECIFICATIONSSeats2 (1 lounged)Filter1 (5.5 m2)Circulation / Massage Pump1 – 370/1500 WMassage Pump-Blower-Disinfection systemOzoneControl box with heater1 – 3000 WChromotherapy LedsMultipointCover1Water Capacity\$50 1Drain Valve\$50 1Voltage20:240 V ~ or 380-415 V ~Max Absorbed Power3370 WFrequency50 Hz | Panels | EcoWood |
| Volume 2.4 m3 EQUIPMENT SPECIFICATIONS 2 (1 lounged) Filter 2 (1 lounged) Filter 1 (5.5 m2) Circulation / Massage Pump 1 – 370/1500 W Massage Pump - Biower - Disinfection system Ozone Control box with heater 1 – 3000 W Chromotherapy Leds Multipoint Cover 1 Water Capacity 850 1 Drain Valve 850 1 Voltage 20-240 V~ or 380-415 V~ Max Absorbed Power 370 W | Weight without water | 300 Kg |
| EQUIPMENT SPECIFICATIONS Seats 2 (1 lounged) Filter 1 (5.5 m2) Circulation / Massage Pump 1 – 370/1500 W Massage Pump - Blower - Disinfection system Ozone Control box with heater 1 – 3000 W Chromotherapy Leds Multipoint Cover 1 Water Capacity 850 I Drain Valve 1 Voltage 200-240 V ~ or 380-415 V ~ Max Absorbed Power 3370 W | Weight with water | 1150 Кg |
| Seats2 (1 lounged)Filter1 (5.5 m2)Circulation / Massage Pump1 - 370/1500 WMassage Pump-Bower-Disinfection systemOzoneControl box with heater1 - 3000 WControl box with heaterMultipointCover1Water CapacitySon 1Drain ValveSon 1Drain Valve20-240 V con 380-415 V con 380-415 V con 380-415 V con 370 WVoltage3270 WMax Absorbed PowerSon 1FrequencySon 1State State St | Volume | 2.4 m3 |
| Filter1 (5.5 m2)Circulation / Massage Pump1 – 370/1500 WMassage Pump-Blower-Disinfection systemOzoneControl box with heater1 – 3000 WControl box with heaterMultipointCover1Water CapacityS50 IDrain Valve1ELECTRICAL SPECIFICATIONS200-240 V ~ or 380-415 V ~Voltage3370 WFrequency50 Hz | EQUIPMENT SPECIFICATIONS | |
| Circulation / Massage Pump1 - 370/1500 WMassage Pump-Blower-Disinfection systemOzoneControl box with heater1 - 3000 WChromotherapy LedsMultipointCover1WATER CIRCUIT SPECIFICATIONSS50 IWater Capacity1Drain Valve1ELECTRICAL SPECIFICATIONS220-240 V ~ or 380-415 V ~Voltage3370 WFrequency50 Hz | Seats | 2 (1 lounged) |
| Massage Pump-Blower-Disinfection systemOzoneControl box with heater1 – 3000 WChromotherapy LedsMultipointCover1WATER CIRCUIT SPECIFICATIONSS50 IWater Capacity850 IDrain Valve1ELECTRICAL SPECIFICATIONS220-240 V ~ or 380-415 V ~Voltage3270 WFrequency50 Hz | Filter | 1 (5.5 m2) |
| Blower-Disinfection systemOzoneControl box with heater1 – 3000 WChromotherapy LedsMultipointCover1WATER CIRCUIT SPECIFICATIONSSo IWater Capacity850 IDrain Valve1ELECTRICAL SPECIFICATIONS220-240 V ~ or 380-415 V ~Voltage3370 WFrequency50 Hz | Circulation / Massage Pump | 1 – 370/1500 W |
| Disinfection systemOzoneControl box with heater1 – 3000 WChromotherapy LedsMultipointCover1WATER CIRCUIT SPECIFICATIONSS0 1Water Capacity850 1Drain Valve1Prain Valve220-240 V ~ or 380-415 V ~Max Absorbed Power3370 WFrequency50 Hz | Massage Pump | - |
| Control box with heater1 – 300 WChromotherapy LedsMultipointCover1WATER CIRCUIT SPECIFICATIONS850 IWater Capacity850 IDrain Valve1ELECTRICAL SPECIFICATIONSVoltage220-240 V ~ or 380-415 V ~Max Absorbed Power3370 WFrequency50 Hz | Blower | - |
| Chromotherapy LedsMultipointCover1WATER CIRCUIT SPECIFICATIONS850 IWater Capacity850 IDrain Valve1ELECTRICAL SPECIFICATIONS20-240 V ~ or 380-415 V ~Voltage3370 WFrequency50 Hz | Disinfection system | Ozone |
| Cover1WATER CIRCUIT SPECIFICATIONSS50 IWater Capacity850 IDrain Valve1ELECTRICAL SPECIFICATIONS20-240 V ~ or 380-415 V ~Voltage220-240 V ~ or 380-415 V ~Max Absorbed Power3370 WFrequency50 Hz | Control box with heater | 1 – 3000 W |
| WATER CIRCUIT SPECIFICATIONSWater Capacity\$50 IDrain Valve1ELECTRICAL SPECIFICATIONSVoltage220-240 V ~ or 380-415 V ~Max Absorbed Power3370 WFrequency50 Hz | Chromotherapy Leds | Multipoint |
| Water Capacity850 IDrain Valve1ELECTRICAL SPECIFICATIONS20-240 V ~ or 380-415 V ~Voltage20-240 V ~ or 380-415 V ~Max Absorbed Power3370 WFrequency50 Hz | Cover | 1 |
| Drain Valve 1 ELECTRICAL SPECIFICATIONS 220-240 V ~ or 380-415 V ~ Voltage 220-240 V ~ or 380-415 V ~ Max Absorbed Power 3370 W Frequency 50 Hz | WATER CIRCUIT SPECIFICATIONS | |
| ELECTRICAL SPECIFICATIONS Voltage 220-240 V ~ or 380-415 V ~ Max Absorbed Power 3370 W Frequency 50 Hz | Water Capacity | 850 I |
| Voltage220-240 V ~ or 380-415 V ~Max Absorbed Power3370 WFrequency50 Hz | Drain Valve | 1 |
| Max Absorbed Power 3370 W Frequency 50 Hz | ELECTRICAL SPECIFICATIONS | |
| Frequency 50 Hz | Voltage | 220-240 V ~ or 380-415 V ~ |
| | Max Absorbed Power | 3370 W |
| Amperage 16A | Frequency | 50 Hz |
| | Amperage | 16A |

Note : the standard measures may vary ±2cm



IMPORTANT: Important: The equipment must be connected to an exclusive and permanent power line capable to support installed power. Lighting and electrical receptacles must be located at least 1.5 meters from the equipment.

The circuit ground wire must be provided to take advantage of the designed-in safety features of the equipment.

The electric installation must be in accordance with actual legislation.