




GRUPO
VIDA DOURADA

LOUNGE CONCEPT IV SUPREME



TECHNICAL INFORMATION

Dimensions	2.20 x 2.40 x 0.80 m
Shell Coril® -	Any color shell
Panels	AluPanels
Weight without water	490 Kg
Weight with water	2140 Kg
Volume	4.2 m3

EQUIPMENT SPECIFICATIONS

Seats	4-6 (with 2 lounged)
Filter	2 (1.1 m2)
Cover	1
Water Capacity	1650 l
Drain Valve	1

TECHNICAL SPECIFICATIONS

Jets	50 *
Circulation Pump	1 – 180 W
Circulation / Massage Pump	-
Massage Pump	2 – 1500 W
Blower	1 – 1030 W
Disinfection system	UV & Ozone
Control box with heater	1 – 3000 W
Illumination Multipoint	RGB Leds


ELECTRICAL SPECIFICATIONS

Voltage	220-240 V ~ or 380-415 V ~
Max Absorbed Power	3370 W
Frequency	50 Hz
Amperage	20A or 3x16A

* Number of jets may depend to the choice of the V-Jets option (standard configuration is C6+A3+E6+G6)

Note : the standard measures may vary ±2cm

Motor compartment must have easy access.



IMPORTANT: Important: The equipment must be connected to an exclusive and permanent power line capable to support installed power. Lighting and electrical receptacles must be located at least 1.5 meters from the equipment.

The circuit ground wire must be provided to take advantage of the designed-in safety features of the equipment.

The electric installation must be in accordance with actual legislation.

Vida Dourada has the right to modify every product in this line and technical data without any forewarning.