



LOUNGE CONCEPT II DESIGN



| TECHNICAL INFORMATION | |
|---|----------------------|
| Dimensions | 2.20 x 1.40 x 0.70 m |
| Shell | White |
| Panels | Alupanels |
| Weight without water | 250 Kg |
| Weight with water | 800 Kg |
| Volume | 2.16 m3 |
| EQUIPMENT SPECIFICATIONS | |
| Seats | 2 lounged |
| Filter | 1 (1.1 m2) |
| Cover | 1 |
| Water Capacity | 550 l |
| Drain Valve | 1 |
| TECHNICAL SPECIFICATIONS | |
| Jets | 35 |
| Circulation Pump | - |
| Circulation / Massage Pump | 1 – 370 / 1500 W |
| Massage Pump | |
| Blower | 1 – 1030 W |
| Disinfection system | Ozone |
| Control box with heater | 1 – 3000 W |
| Illumination | Multipoint RGB Leds |
| ELECTRICAL SPECIFICATIONS | |
| Voltage | 220-240 V ~ |
| Max Absorbed Power | 3370 W |
| Frequency | 50 Hz |
| Amperage | 16A |
| Noto: the standard measures may yary +2cm | |

Note : the standard measures may vary ±2cm



IMPORTANT: Important: The equipment must be connected to an exclusive and permanent power line capable to support installed power. Lighting and electrical receptacles must be located at least 1.5 meters from the equipment.

The circuit ground wire must be provided to take advantage of the designed-in safety features of the equipment.

The electric installation must be in accordance with actual legislation.

Vida Dourada has the right to modify every product in this line and technical data without any forewarning.